




# SIM900\_EVB kit\_ User Guide\_V1.04



<b>Document Title:</b>	SIM900 EVB kit User Guide
<b>Version:</b>	1.04
<b>Date:</b>	2011-08-23
<b>Status:</b>	Release
<b>Document Control ID:</b>	SIM900_EVB kit_User Guide_V1.04

### General Notes

SIMCom offers this information as a service to its customers, to support application and engineering efforts that use the products designed by SIMCom. The information provided is based upon requirements specifically provided to SIMCom by the customers. SIMCom has not undertaken any independent search for additional relevant information, including any information that may be in the customer's possession. Furthermore, system validation of this product designed by SIMCom within a larger electronic system remains the responsibility of the customer or the customer's system integrator. All specifications supplied herein are subject to change.

### Copyright

This document contains proprietary technical information which is the property of SIMCom Limited., copying of this document and giving it to others and the using or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights reserved in the event of grant of a patent or the registration of a utility model or design. All specification supplied herein are subject to change without notice at any time.

*Copyright © Shanghai SIMCom Wireless Solutions Ltd. 2010*

## Contents

Contents .....	3
Version History .....	4
1. SIM900 EVB .....	5
2. EVB APPLICATION .....	7
3. EVB Accessory .....	7
4. Accessory Interface .....	8
4.1 Power Interface .....	8
4.2 Audio Interface .....	9
4.3 SIM card interface .....	10
4.4 Antenna Interface .....	11
4.5 Serial port Interface .....	11
4.6 LED Indicator .....	12
5. Test Interface .....	14
5.1 J103 .....	14
5.2 J201 .....	15
5.3 J104 .....	16
6. EVB and Accessory .....	17
7. Illustration: .....	18
7.1 Power on module: .....	18
7.2 Registering Network and making a call .....	18
7.3 Downloading .....	22
7.4 Turn off .....	22

## Figure Index

FIGURE 1: EVB TOP VIEW .....	5
FIGURE 2: EVB BOTTOM VIEW .....	6
FIGURE 3: EVB ACCESSORY .....	7
FIGURE 4: POWER INTERFACE .....	8
FIGURE 5: AUDIO INTERFACE .....	9
FIGURE 6: SIM CARD INTERFACE .....	10
FIGURE 7: ANTENNA INTERFACE .....	11
FIGURE 8: SERIAL PORTS .....	11
FIGURE 9: LED INDICATOR .....	12
FIGURE 10: TEST INTERFACE OVERVIEW .....	14
FIGURE 11: J103 INTERFACE .....	14
FIGURE 12: J201 INTERFACE .....	15
FIGURE 13: J104 INTERFACE .....	16
FIGURE 14: EVB AND ACCESSORY .....	17

## Version History

Data	Version	Description of change	Author
2009-12-08	1.01	Origin	Lee
2010-07-01	1.02	§6.1 Add notice: You should equip four sets of screws for better grounding to achieve a better performance.	Jerry
2010-12-22	1.03	§6.2 Add the Hyper Terminal setting. Update the figures: 1,2,6,7,10,11,12,13	Jerry
2011-08-23	1.04	§1 Update the discripiton. G: Module TE interface §2 Add the chapter 2 EVB APPLITION	zhaojuntao

## SCOPE

This document describes how to use SIM900 EVB to do test; user can get useful info about the SIM900 EVB quickly through this document.

This document is subject to change without notice at any time.

## 1. SIM900 EVB





Figure 1: EVB TOP view



**Figure 2: EVB BOTTOM view**

- A: DC jack
- B: MAIN serial port
- C: DEBUG serial port
- D: SIM card holder
- E: Test point
- F: Antenna fix hole
- G: Module-TE interface ( The interface compatible with SIM900-TE , SIM900D-TE and SIM800E-TE)
- H: Module fix hole
- I: Reset key
- J: Power key
- K: Charge switch
- L: Download switch
- M: Power switch
- N: Headphones jack
- O: Headset jack
- P: Line in jack
- Q: LED indicator

## 2. EVB APPLICATION

SIM900-EVB can work with the SIM900, SIM900D and SIM800E modules. The Module-TE interface of EVB is compatible with SIM900-TE, SIM900D-TE and SIM800E-TE. The modules supported by SIM900-EVB is listed as below:

1. SIM900
2. SIM900D
3. SIM800E

## 3. EVB Accessory




Figure 3: EVB Accessory

- A: Antenna
- B: Antenna cable
- C: 5V DC adapter
- D: Serial Port cable

## 4. Accessory Interface

### 4.1 Power Interface





Figure 4: Power Interface

Pin	Signal	I/O	Description
1	Adapter input	I	5V/2.0A DC source input

## 4.2 Audio Interface



**Figure 5: Audio Interface**

### Headset interface:

Pin	Signal	I/O	Description
1	MIC1P	I	Positive microphone input
2	SPK1P	O	Positive receiver output
3	MIC1N	I	Negative microphone input
4	SPK1N	O	Negative receiver output

### Earphone interface:

Pin	Signal	Input/Output	Description
5	MIC2P&SPK2P	I/O	Auxiliary audio input/output

### Line in interface:

Pin	Signal	Input/Output	Description
6	Line in R/L	I	Line in input

#### 4.3 SIM card interface




Figure 6: SIM card interface

#### 4.4 Antenna Interface



Figure 7: Antenna Interface

#### 4.5 Serial port Interface




Figure 8: Serial Ports

Serial Port 1——MAIN Interface

Serial Port 2——DEBUG Interface


**Main Interface:**

Pin	Signal	I/O	Description
1	DCD	O	Data carrier detection
2	TXD	O	Transmit data
3	RXD	I	Receive data
4	DTR	I	Data Terminal Ready
5	GND		GND
7	RTS	I	Request to Send
8	CTS	O	Clear to Send
9	RI	O	Ring Indicator

**Debug Interface:**

Pin	Signal	I/O	Description
2	DEBUG_TX	O	Transmit data
3	DEBUG_RX	I	Receive data
5	GND		GND

#### 4.6 LED Indicator



**Figure 9: LED Indicator**

Working state of LED as list:

Name	Description	STATUS
Q1	Power ON/OFF indicator	Bright: EVB Power ON; Extinct: EVB Power OFF
Q2	Module status indicator	Bright: Module runs normally Extinct: System is powered down
Q3	GSM_NET status indicator	Blinking at a certain frequency according various GSM net status

## 5. Test Interface




Figure 10: Test interface overview

### 5.1 J103




Figure 11: J103 Interface

#### J103 Interface Pin List:

Pin	Signal	I/O	Description
1	DISP_D/C	O	Display data or address select
2	DISP_CS	O	Display select output
3	DISP_CLK	O	Display clock output
4	DISP_DATA	O	Display data
5	GPIO12	I/O	GPIO
6	ADC	I	ADC input
7	GPIO11	I/O	GPIO
8	TEMP_BAT	I	ADC input
9	SIMPRESENCE	I	SIM detect input
10	PWM1	O	PWM output 1
11	SDA	I/O	I2C BUS DATA
12	SCL	O	I2C BUS CLOCK

13	GND	/	GND
14	PWM2	O	PWM output 2

## 5.2 J201




Figure 12: J201 Interface

### J201 Interface Pin List:

Pin	Signal	I/O	Description
1	TXD	O	Transmit data
2	RXD	I	Receive data
3	DCD	O	Data carrier detection
4	RI	O	Ring Indicator
5	CTS	O	Clear to Send
6	GND	/	GND
7	DTR	I	Data Terminal Ready
8	DEBUG_RX	I	Receive data
9	RTS	I	Request to Send
10	DEBUG_TX	O	Transmit data

### 5.3 J104




Figure 13: J104 Interface

#### J104 Interface Pin List:

Pin	Signal	I/O	Description
1	GPIO10	I/O	
2	GPIO5	I/O	
3	GPIO9	I/O	
4	GPIO4	I/O	
5	GPIO8	I/O	
6	GPIO3	I/O	
7	GPIO7	I/O	
8	GPIO2	I/O	
9	GPIO6	I/O	
10	GPIO1	I/O	
11	PWRKEY_OUT	O	POWER KEY OUT
12	PWRKEY	I	POWER KEY IN
13	VDD_EXT	POWER	VEXT
14	VBAT	POWER	POWER

## 6. EVB and Accessory

The EVB and its accessory are equipped as the Figure 14



**Figure 14: EVB and Accessory**

## 7. Illustration:

### 7.1 Power on module:

- (1) Connect the Module-TE to the 60pins connector on SIM900 EVB, plug in 5V DC adapter, switch S105 to "ON" state; keep S101 and S102 at "OFF" state,
- (2) Press the PWRKEY for more than 1 second and then release, the module power on.

After the module is powered on, the light Q3 will flash at a certain frequency. Through the state of LED, you can judge registering status of the module. For detailed description, please refer to the module HD spec.


*Note: You should equip four sets of screws for better grounding to achieve a better performance.*

### 7.2 Registering Network and making a call

- (1) Connect the antenna to the Module-TE, insert SIM card and earphone.
- (2) Connect the serial port cable to the MAIN serial port; Open the Hyper Terminal (AT command windows) on your computer.



#### First, check the serial port number:

My computer (right click) → Manage → Device Manager → Ports (COM&LPT)




#### Second, use the Hyper Terminal to call the module as following:


- a. Open the HyperTerminal
- START→All Programs→Accessory→Communication→HyperTerminal.



b. Configure the serial port number




c. Set the baud rate and flow control




User can set the baud rate from 1200bps to 115200bps, and the flow control set to "None"

- (3) Act on the step of running which mentioned above, power on the module, typing the AT command in the HyperTerminal, and then the module will execute its corresponding function.
- Connect the module.



Click the “call” icon.

- Typing the AT command. When module is powered on with autobauding enabled, user must firstly send “AT” to synchronize the baud rate. The default setting of the module is autobauding.
- Use AT command to make a call.



```
AT
OK
AT+CSQ
+CSQ: 28,0

OK
AT+CPIN?
+CPIN: READY


OK
AT+CREG
ERROR
AT+CREG?
+CREG: 0,1

OK
ATD92523408;
OK
ATH
OK
-
```

A screenshot of the HyperTerminal application window titled "021 - HyperTerminal". The window has a menu bar with File, Edit, View, Call, Transfer, Help. Below the menu is a toolbar with icons for file operations like Open, Save, Print, and a call icon. The main text area shows a series of AT command interactions. At the bottom of the window, there is a status bar with "Connected 0:00:25" and several control buttons: Auto detect, 115200 8-N-1, SCROLL, CAPS, NUM, Capture, and Print echo.

### 7.3 Downloading

Connect the serial port cable to the **MAIN** serial port, plug 5V DC adapter, open the download tool and click the START key, switch the S105 and S102 to “ON” state. An example of SIM900 is show as below.



### 7.4 Turn off

Turn off the module: press the PWRKEY for about 2 seconds, the module will be turned off.

**Contact us:****Shanghai SIMCom Wireless Solutions Ltd.**

Add: SIM Technology Building, No.633, Jinzhong Road, Changning District, Shanghai P.R. China  
200335

Tel: +86 21 3235 3300

Fax: +86 21 3235 3301

URL: [www.sim.com/wm](http://www.sim.com/wm)